


G4 4.4A 6V&12V

(1.1A X 4)



UltraSafe[®] Battery Charger[™]

Charge Fully Drained Batteries Up To **40Ah**.
Maintain All Battery Sizes.

ATVs, Lawn Mowers, Motorcycles, Cars, Trucks, Boats, RVs, Tractors, Equipment, And More.

Ultra-compact, rugged, and portable **UltraSafe[®]** Smart Charger. Features **spark proof technology** and **reverse polarity protection**. Charges **2X faster** than ordinary chargers. Stay connected 24/7 with **zero overcharge**.



Start-Stop.

Counteracts increased cyclic energy demands placed on batteries in micro-hybrid vehicles.



Firewall.

Multi-level safety barrier prevents unsafe and abnormal conditions.



Optimization.

Stabilizes internal battery chemistry for increased performance and longevity.



Load Tracking.

Dynamically changes charge current when a load is placed on the battery.



Diagnostics.

Intuitive visual diagnostic tool for detecting reverse polarity, low-voltage or damaged batteries.



Energy Save.

Minimizes energy consumption when full power is not needed.



Thermal Monitor.

Internal temperature sensors adjust charge based on ambient climate.



Safe.

Protects against reverse polarity, sparks, over-charging, overcurrent, open-circuits and overheating.



Memory.

Returns to last-selected mode when restarted.



Interactive.

Alters the charging process based on organic battery feedback.



Recovery.

Applies a high-voltage pulse charge when low-voltage, sulfation, or lost capacity is detected.



Rugged.

Dirt, water, UV, impact and crush resistant.



CANBUS.

Automatically enables the charging port to charge CANBUS systems.



Maintenance Plus.

Keeps the battery fully charged without over-charging, indefinitely.

Charge **6V&12V** Batteries Up To 40Ah. Maintain All Battery Sizes.



no.co

NOCO
Since 1914


Charging Modes

| Mode | Explanation | |
|--------------|---|--|
| Standby | No Power In standby mode, the charger is not charging or providing any power to the battery. Energy Save is activated during this mode, drawing microscopic power from the electrical outlet. When selected, an orange LED will illuminate. | |
| 12V NORM | 14.5V 1.1A Up To 40Ah Batteries For charging 12-volt Wet Cell, Gel Cell, Enhanced Flooded, Maintenance-Free and Calcium batteries. When selected, a white LED will illuminate. | 6V NORM Press & Hold 7.25V 1.1A Up To 40Ah Batteries For charging 6-volt, Wet Cell, Gel Cell, Enhanced Flooded, Maintenance-Free and Calcium batteries. When selected, a white LED will illuminate. |
| 12V COLD/AGM | 14.8V 1.1A Up To 40Ah Batteries For charging 12-volt batteries in cold temperatures below 50°F (10°C) or AGM batteries. When selected, a blue LED will illuminate. | 12V LITHIUM Press & Hold 14.2V 1.1A Up To 40Ah Batteries For charging 12-volt lithium-ion batteries, including lithium iron phosphate. When selected, a blue LED will illuminate. |

Technical Specifications

| | | | |
|------------------------|------------------------------|----------------------|--|
| Input Voltage AC: | 110-120 VAC, 50-60Hz | Type of Batteries: | 6V & 12V |
| Working Voltage AC: | 85-130 VAC, 50-60Hz | Battery Chemistries: | Wet, Gel, MF, CA, EFB, AGM, LIB |
| Efficiency: | 85% Approx. | Battery Capacity: | Up To 40Ah (12V), Up To 40Ah (6V), Maintains All Battery Sizes |
| Power: | 84W Max | | |
| Low-Voltage Detection: | 2V (12V), 2V (6V) | Housing Protection: | IP64 |
| Back Current Drain: | <5mA | Cooling: | Natural Convection |
| Ambient Temperature: | 0°C to +40°C, 32°F to +104°F | Dimensions (LxWxH): | 9.2 x 9.2 x 2.4 in (234 x 234 x 61mm) |
| Charger Type: | 8 Step, Smart Charger | Weight: | 2.78 Pounds (1.26 kg) |

Charging Steps



What's In The Box

- G4 Smart Charger
- (2) Battery Clamp Connectors w/ Integrated Eyelets
- (4) 10' Extension Cables
- User Guide and Information Guide & Warranty

4-Banks

Independently charge up to **4 different batteries** at the same time with the G4. Each of the four banks is **1.1A**, charges batteries up to **40Ah**, and will remember the last selected mode.

Retail Packaging:

Dimensions: 10.31"x10.24"x4.80"
 (262 x 260 x 122mm)
 Weight: 5.80lbs (2.63kg)
 UPC: 0-46221-11091-3

Inner Carton:

Dimensions: 10.55"x5.12"x10.71"
 (268 x 130 x 272mm)

(cont'd.) Weight: 6.37lbs (2.89kg)

Master Carton:


Dimensions: 21.89"x11.02"x11.42"
 (556 x 280 x 290mm)
 Weight: 26.98lbs (12.24kg)
 Quantity: 4

UCC: 10046221110910

Units Per Pallet: 120 Units



CONFORMS TO UL STD. UL1236
 CERTIFIED TO CSA STD. C22.2 No.107.2



AC Cable: 75 in
 (190.5cm)

DC Cable: 56 in
 (142.24cm)



no.co

NOCO
 Since 1914